



REFERENCE DRAWINGS	No.
GENERAL CONVEYOR PROFILE	SAROOJ - LYT - GL - DR - 002

NOTES
1. A LADDER WITH A WIDTH OF 15 CM IS USED AS A CABLE TRAY. 2. A LADDER WITH A WIDTH OF 10 CM IS USED AS A CABLE TRAY FOR THE INSIDE OF THE DOLPHINS.

SYMBOL & LEGEND / ABBREVIATION	
	Ladder as Cable Tray
	Transformer Rectifier
	Test Point
	Positive Box
	Negative Box
	Negative Cable
	Positive Cable TR1
	Positive Cable TR2
	Positive Cable TR3
	Positive Cable TR4
	Anode

02	1.6.2025	ISSUED FOR APPROVAL	M.M	M.M	M.SH	—
02	12.23.2024	ISSUED FOR REVIEW	M.M	M.M	M.SH	—
01	11.20.2024	ISSUED FOR REVIEW	M.M	M.M	M.SH	—
00	11.09.2024	ISSUED FOR REVIEW	M.M	M.M	M.SH	—
REV.	DATE	DESCRIPTION	PREP.	CHK.	APPR.	AUTH.
OWNER:						
ASIAYE ARAM Co.						
EPS CONTRACTOR:						
			FARA SANAT BAN ENG. CO.			
VENDOR:						
PROJECT TITLE:						
CATHODIC PROTECTION SYSTEM						
DRAWING TITLE:						
Placement of Cable Support						
DOCUMENT CLASS:—			OWNER CONTRACT No.:—			
VENDOR DWG No.:—						
						SC: AS SHOWN
						SIZE: A0
DOCUMENT No.						
NPT Doc.	PLANT No.	REQ. No.	TYPE&CODE	SEQ.	REV.	SHEET NO.
—	—	—	—	XXX	03	0F 1